		•			
			**		
	•				
	-				
	1				
•					
•					
				-	
					-
					-
			-		
					•

	Reg. No. :												-
--	------------	--	--	--	--	--	--	--	--	--	--	--	---

# Question Paper Code: 50494

### B.E./B.Tech. DEGREE EXAMINATIONS, APRIL/MAY 2023.

#### Fifth Semester

Electronics and communication Engineering

#### EC 8501 — DIGITAL COMMUNICATION

(Regulations 2017)

Time: Three hours

Maximum: 100 marks

## Answer ALL questions.

PART A —  $(10 \times 2 = 20 \text{ marks})$ 

- 1. State the source coding theorem with necessary equation.
- 2. How do you define the information contained in a symbol  $S_k$  that occurs with probability  $P_k$ ?
- 3. What is slope overload distortion?
- 4. What is the expression for the zero-frequency value of power spectral density of a stationary process?
- 5. Define inter symbol interference.
- 6. Find the impulse response of a filter that is matched to a pulse signal g(t) of duration T.
- 7. What is Gray coding? Show the QPSK constellation with Gray coded bit mapping.
- 8. Write the bit error rate expression of coherent BPSK.
- 9. State the channel coding theorem.
- 10. What is a linear block code?

# PART B — $(5 \times 13 = 65 \text{ marks})$

11.	(a)	(i)	Find the entropy of a binary memoryless source as a function of (probability of occurrence of symbol-0). Find the entropy (1) p <sub>0</sub> =0, (2) p <sub>0</sub> =1. Derive the value of p <sub>0</sub> for which the entropy maximized. With these values, plot the entropy.							
		(ii)	What is a source encoder? State source-coding theorem.	(5)						
			Or							
	(b)									
			$x_1$ $x_1$ $x_2$ $x_3$ $x_4$ $x_5$ $x_6$							
			$P(x_i)$ 0.30 0.25 0.20 0.12 0.08 0.05							
		(i)	Find the Huffman encoding of the source given in Table 1.	(8)						
		(ii)	Find the entropy, average code length, and the code efficiency of code from Huffman encoding.	the (5)						
12.	(a)	For the delta modulation (DM):								
		(i)	Illustrate the DM process with staircase approximation wavefor $m_q(t)$ .	orm (3)						
		(ii)	Explain the transmitter and receiver of delta modulator with ble diagrams.	ock (8)						
		(iii) Illustrate granular noise in delta modulation.								
			Or							
	(b)	Drav	w and explain the line coding waveform and its power spectrum for	r:						
		(i)	Unipolar nonreturn-to-zero (NRZ) signaling	(3)						
		(ii)	Polar nonreturn-to-zero (NRZ) signaling	(2)						
		(iii)	Unipolar return-to-zero (RZ) signaling	(3)						
		(iv)	Bipolar return-to-zero (BRZ) signaling	(2)						
		(v)	Manchester code signaling	(3)						
13.	(a)	(i)	What is the Nyquist criterion for distortion less baseba	and (8)						
		(ii)	Show an ideal pulse shape that satisfies Nyquist criterion.	(5)						
			$\operatorname{Or}$							
	(b)	SNR	ve the impulse response of receiver filter that maximizes the received. Assume the received pulse signal g(t) is corrupted by additive whe ssian noise w (t) at the receiver.							

14.	(a)	Dra	aw and explain the following:	
		(i)	Differential phase shift keying transmitter.	(7
		(ii)	Differential phase shift keying receiver.	(6
			${ m Or}$	
	(b)	(i)	Draw and explain the generation of coherent QPSK signal.	(7
		(ii)	Illustrate and describe the detection of coherent QPSK signal.	(6)
15.	(a)	(i)	With block diagrams and equations, explain the use of gene matrix and parity check matrix in systematic codes.	erator (8)
		(ii)	How do you generate syndrome for the systematic codes? Write properties of syndrome.	te the
			$\mathbf{Or}$	
	(b)	(i)	What are cyclic codes?	(2)
		(ii)	State the two properties of cyclic codes.	(3)
		(iii)	Prove the cyclic property of cyclic codes.	(8)
			PART C — $(1 \times 15 = 15 \text{ marks})$	
16.	(a)		sider a binary symmetric channel with $P(x_1) = \alpha$ and transpability p.	sition
		(i)	Find the mutual information I(X;Y) in terms of H(Y) and p.	(8)
		(ii)	Calculate I(X;Y) for $\alpha = 0.5$ and $p = 0.1$	(4)
		(iii)	Repeat (ii) for $\alpha$ = 0.5 and p = 0.5 and comment on the result.	(3)
			$\mathbf{Or}$	
	(b)		ate $\frac{1}{2}$ convolutional encoder with constraint length of 3 uses exator sequences: $g_1 = (111)$ and $g_2 = (101)$ .	s the
		(i)	Sketch encoder diagram.	(3)
		(ii)	Draw the state diagram for the encoder.	(4)
		(iii)	Determine the d <sub>free</sub> distance of the encoder.	(8)

**50494** 3 **50494**