Kes								

Question Paper Code: 20924

B.E./B.Tech. DEGREE EXAMINATIONS, NOVEMBER/DECEMBER 2023.

Third Semester

Electronics and Communication Engineering

EC 3351 - CONTROL SYSTEMS

(Common to Electronics and Telecommunication Engineering)

(Use of Semi-log graph and Polar graph and Normal graph sheet is permitted)

(Regulations 2021)

Time: Three hours

Maximum: 100 marks

Answer ALL questions.

PART A —
$$(10 \times 2 = 20 \text{ marks})$$


- 1. Define transfer function of a system.
- 2. Write Masons Gain formula.
- 3. What is the significance of integral mode in a PID controller?
- 4. List the time domain specifications of second order system.
- 5. Define Gain Margin.
- 6. When lag-lead compensator is required?
- 7. Define BIBO stability.
- 8. State Routh-Hurwitz criterion for stability.
- 9. What is state variable?
- 10. Define Controllability and Observability.

PART B —
$$(5 \times 13 = 65 \text{ marks})$$

11. (a) Derive the transfer function of armature controlled DC servo motor system. (13)

 Ω_1

(b) Using block diagram reduction technique, obtain the closed loop transfer function for the following system. (13)



- 12. (a) (i) The open loop transfer function of the mechanical system is given by $G(s) = \frac{10(s+2)}{s(s+1)(s+3)}$. Find the type of input signal that will provide rise to a constant steady state error and calculate its values. (7)
 - (ii) Discuss about PI controller with suitable electronic circuit and derive its transfer function. (6)

Or

- (b) The open loop transfer function of a unity feedback system is given by $G(s) = \frac{25}{s(s+5)}$. Obtain the rise time, peak time and settling time when the system is subjected to unit step input. (13)
- 13. (a) The open loop transfer function of the system, $G(s) = \frac{1}{s(4s+1)(0.5s+1)}$. Sketch the polar plot and obtain the value of gain margin and phase margin. (13)

Or

- (b) Derive the frequency domain specifications of second order system. (13)
- 14. (a) (i) The open loop transfer function of feedback control system is given by $G(s) = \frac{K}{(s^2 + 6s + 25)(s^2 + 6s + 8)}$. Using Routh criterion, determine the range of K and frequency of oscillation of the system.

(8)

(ii) Discuss in detail about relative stability in control systems. (5)

Or


- (b) Sketch the root locus plot for the unity feedback system whose open loop transfer function is given by $G(s) = \frac{K}{s(s^2 + 6s + 1)}$. (13)
- 15. (a) (i) Determine the canonical state model of the system whose transfer function given as $\frac{Y(s)}{U(s)} = \frac{2s+10}{(s+2)(s+3)(s+4)}$. (7)
 - (ii) A linear time invariant system is described by the following state model. (6)

$$\begin{bmatrix} \dot{x}_1 \\ \dot{x}_2 \end{bmatrix} = \begin{bmatrix} 1 & 0 \\ 1 & 1 \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} \text{ and Initial state vector, } X_0 = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

Compute the solution of homogeneous state equation.

Or

(b) Construct the state model of the give mechanical system.



PART C —
$$(1 \times 15 = 15 \text{ marks})$$

- 16. (a) (i) Derive the solutions of Homogeneous state equations. (9)
 - (ii) Determine the state controllability of the following system. (6)

$$\begin{bmatrix} \dot{x}_1 \\ \dot{x}_2 \\ \dot{x}_3 \end{bmatrix} = \begin{bmatrix} 0 & 0 & 1 \\ -2 & -3 & 0 \\ 0 & 2 & 3 \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ x_3 \end{bmatrix} + \begin{bmatrix} 0 \\ 2 \\ 0 \end{bmatrix} \text{ u and } y = \begin{bmatrix} 1 & 0 & 0 \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ x_3 \end{bmatrix}$$

Or

- (b) A unity feedback system has an open loop transfer function, $G(s) = \frac{K}{s(s+1)}$. Design a suitable phase lead compensator to satisfy the following specifications.
 - (i) The phase margin of the system is ≥ 45°
 - (ii) Steady state error for a unit input $\leq 1/15$
 - (iii) The gain crossover frequency of the system must be less than 7 rad/sec. (15)

(13)